

Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Alaska - Warehousing needs greatly focus on space-saving techniques and layout to maximize expensive square footage and decrease travel time needed to get goods from the loading docks and from point A to point B. Extremely narrow aisles offer more storage space since there is less space needed for aisle access. Configuring the warehouse is known as warehouse optimization. Warehouse Optimization Several benefits can be enjoyed for adding very narrow aisle warehouse optimization such as more storage space for the facility. Since very narrow forklift trucks have been designed to take up significantly less space, warehouse aisle widths can be reduced to half the width needed by traditional forklifts. Certain models of very narrow aisle forklifts can increase the square foot storage capabilities by delivering greater stacking heights. Very narrow aisle forklifts can greatly reduce costs compared to traditional forklifts since the same amount of stock takes up less space in the warehouse. In most urban areas where square footage is very costly, this is a huge benefit to warehouse operations. Adding a very narrow aisle width system can increase storage up to eighty percent when planned properly. This warehouse design creates more rack faces and increased product access. This usually equates to less travel time gathering and storing product as more product is located within a smaller, more accessible area. It is common for warehouses to use a very narrow or narrow aisle layout. Less than eleven feet of aisle width is needed by narrow aisles. Very narrow aisles reduce the aisle width further to around six-and-a-half feet. Either of these widths drastically increases storage potential. Using a forklift for order picking and stocking can be difficult in these aisle widths, especially when turning. To meet these challenges, several different types of very narrow forklifts have been specially developed for various types of tasks to allow easier maneuvering in narrow aisle widths. It is necessary to know the dimensions of the aisle when selecting a forklift for a certain job. It is important to have the correct aisle dimensions before forklift shopping to avoid securing a machine that won't fit its' intended location. Taking note of any utilities, columns or posts is necessary before choosing a particular narrow aisle forklift design to maximize warehouse optimization and safety. Very Narrow Aisle Forklift Trucks Rechargeable batteries are typical for powering very narrow aisle forklift trucks and most models are electric. These very narrow aisle trucks are more commonly available as standup riders, which helps increase productivity and operator comfort. There are different very narrow aisle forklift designs such as order pickers, reach trucks, wing-mast or turret and end-control riders. Reach Forklift Trucks Reach trucks were designed as a version of the rider stacker forklift but specially modified for use in narrow aisles. This machine earned its name by its ability to reach its forks to secure a load. The two kinds of reach trucks the moving carriage and the moving mast. The moving carriage works by raising and lowering the carriage and the driver. While the operator stays at ground level, the moving mast is responsible for raising and lowering the forks. The moving mast reach truck is generally considered the safer of the two types of reach trucks. Reach trucks utilize a pantograph system that is a jointed framework design enabling the driver to place and reach loads without moving the forklift. Order Pickers Order pickers have been designed and developed specifically for use in picking orders from high, typically hard-to-reach racks. Order pickers are specific for lighter stock items that can be lifted by hand. These order pickers work by lifting the operator up to the level of goods in order to identify and pick the specific item or items necessary to fill an order. End-Control Riders End-control riders are machines that pick loads up at floor level and move the items horizontally as opposed to lowering or lifting over numerous heights. Turret or Swing-Mast Forklift The turret or swing mast very narrow aisle forklifts have a swivel mast that pivots and articulates. Pallets can be set on either the right or left side of the forklift due to the machine's ability to use its' swinging mast. Guided Very Narrow Aisle Trucks Rail or wire can guide the very narrow aisle forklift trucks down the aisle securely. Thanks to the guide rails, the possibility of crashing into racks is greatly reduced. In rail-guided models, sets of rails are placed into the floor on each side of the aisle. They run the

length of the aisle and also curve around the aisles' edge. Specific wheel guides are on the forklift. These slide into the rails to stop the forklift from moving out of the rail guards. Running down the center of the aisle, wire-guidance forklifts rely on floor wires instead of rails. The wire-guides function similarly to the rail systems except the forklift has a wire-guide system to prevent the machine from traveling where it is not supposed to. Work Site Considerations To use a narrow aisle configuration, there are some key considerations that need to be made. The narrow aisle units feature tall racking systems. The floor construction and the racks need to be carefully taken into account for everyone's safety. Four specific areas need to be perfectly prepared before a racking system can be implemented including a level floor, plumb racks, any floor cracks need to be repaired and the floor's load capacity must be accurate. These locations need to be maintained and monitored continuously. Level Floor Because of the height of the racking systems, any slight slope of the floor is likely to negatively affect the plumbness of the racks, especially over time when loads are continuously placed and removed on the racks. A level floor is vital for the safety and integrity of the operator, employees, stock and the warehouse. Crack Repair When there are floor cracks found, they need to be assessed and immediately fixed for safety concerns. Safety can become compromised when flooring cracks become 3/8 inches wide. They require proper filling with a substance that is as hard as the floor. Floor Load Capacity Minimum flooring requirements must be met before considering a narrow aisle installation. At a minimum, the floor should consist of 3,000 psi concrete as well as contain evenly distributed rebar approximately 3 to 4 inches below the surface. Extra reinforcements might be needed depending on the load requirements and the configuration. Plumb Racks Of great importance is the proper installation of the racking system. There is a major chance of rack failure if improper installation occurs. One of the most important details to ensure proper installation, is that all racks are plumb. If necessary, rack shims should be used to ensure the racks are plumb within 1 inch at the 30 foot height of the racks. If the above measures are not taken or are improperly implemented, it is likely to cause a racking failure. Such failure is likely to result in costly damage to goods, the warehouse facility, forklifts and, worst of all, employees could be significantly injured or even killed. Because of these reason, these measures are the most important part of implementing a narrow aisle configuration for warehousing optimization.